

Eaton 171295

Catalog Number: 171295

Eaton Moeller® series SL4 Complete device;red-green; LED;24 V;including base 100mm



General specifications

Product Name	Catalog Number
Eaton Moeller® series SL4 Signal tower	171295
EAN	Product Length/Depth
4015081678389	72 mm
Product Height	Product Width
279 mm	72 mm
Product Weight	Certifications
0.209 kg	UL report applies to both US and Canada
	UL Category Control No.: NKCR
	CSA Class No.: NKCR7
	CSA-C22.2 No. 94-91
	IEC/EN 60947-5-1
	CE
	UL 508
	Certified by UL for use in Canada
	UL
	UL File No.: E29184
	CSA-C22.2 No. 14-10
	IEC/EN 60529
Catalog Notes	Model Code
The value specified for the leakage current shall apply per module.	SL4-100-L-RG-24LED

Features & Functions

Color

Red

Green

Fitted with:

100 mm tube

Foot

Light modules

LED

Number of modules

2

General

Connection to SmartWire-DT

No

Current consumption

0.022 - 0.033 A, at 24 V AC/DC

The value specified for the current consumption at 24 V AC/DC applies to each module.

Degree of protection

IP66

NEMA 4X, 13

Lifespan, electrical

100,000 h

Light type

Continuous light

Loudness

0 dB

Material

Cap: Polycarbonate (PC)

Enclosure: Polycarbonate (PC)

Mounting position

As required

Overvoltage category

III

Pollution degree

3

Product Category

SL signal towers

Radiation angle

360 °

Rated impulse withstand voltage (Uimp)

4000 V AC

Shock resistance

Mechanical, According to IEC/EN 60068-2-27

15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

Type

Complete device

Voltage type

AC/DC

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

Terminal capacities

Terminal capacity

0.2 - 1.5 mm², solid or flexible conductor

0.25 - 0.75 mm², flexible with ferrule with plastic collar

0.25 - 1.5 mm², solid or flexible with ferrule

24 - 16 AWG

Electrical rating

Leakage current

0.003 A

Rated insulation voltage (Ui)

250 V

Rated operational voltage

24 V AC/DC

24 V AC/DC ± 10 %

Rated operational voltage (Ue) - min

24 V

Rated operational voltage (Ue) - max

24 V

Risorse

Disegni

[eaton-operating-sl4-complete-device-dimensions.eps](#)

[eaton-operating-sl7-continuous-light-symbol-002.eps](#)

[eaton-operating-sl4-complete-device-3d-drawing.eps](#)

[eaton-operating-module-sl7-complete-device-symbol-003.eps](#)

eCAD model

[DA-CE-ETN.SL4-100-L-RG-24LED](#)

Istruzioni di installazione

[IL047001ZU](#)

[IL047002ZU](#)

mCAD model

[DA-CD-sl4_100_l_rg_24led](#)

DA-CS-sl4_100_L_rg_24led

Report di certificazione

DA-DC-00004253.pdf

DA-DC-00004257.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Eaton is a registered trademark.

All other trademarks are
© 2024 Eaton. Tutti i diritti property of their respective
riservati.



Eaton.com/socialmedia